

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification ⁷ : H01L 21/00, C23C 16/48	A1	(11) International Publication Number: WO 00/05753 (43) International Publication Date: 3 February 2000 (03.02.00)
--	-----------	--

(21) International Application Number: PCT/US99/16583

(22) International Filing Date: 21 July 1999 (21.07.99)

(30) Priority Data:
09/122,620 23 July 1998 (23.07.98) US(71) Applicant: APPLIED MATERIALS, INC. [US/US]; 3050
Bowers Avenue, Santa Clara, CA 95054 (US).(72) Inventor: ANDERSON, Roger, N.; 1824 Nestorita Way, San
Jose, CA 95124 (US).(74) Agents: BERNADICOU, Michael, A. et al.; Blakely, Sokoloff,
Taylor & Zafman L.L.P., 7th floor, 12400 Wilshire Boulevard,
Los Angeles, CA 90025 (US).(81) Designated States: JP, European patent (AT, BE, CH, CY, DE,
DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).**Published***With international search report.**Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.*

(54) Title: INFRA-RED TRANSPARENT THERMAL REACTOR COVER MEMBER



(57) Abstract

A cover member for a semiconductor processing thermal reactor, comprising a central quartz window portion and an outer flange portion. The central window portion has either an inward bow defining a concave outside surface, or an outward bow defining a convex outside surface. The centerline of the central window portion has a radius of curvature which when extended through the flange portion divides the flange portion into an upper flange section and a lower flange section. The upper and lower flange portions having substantially equal masses.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INFRA-RED TRANSPARENT THERMAL REACTOR COVER MEMBER

FIELD OF THE INVENTION

The present invention relates to thermal reactors for processing semiconductor wafers, and more particularly to a reactor having a domed window with the center of mass equally distributed within the flange portion of the window.

BACKGROUND OF THE INVENTION

Recent technological progress is closely identified with the increasing miniaturization of electronic circuits made possible by advances in semiconductor processing. Certain advanced processing techniques require exposing a semiconductor structure to a reactant gas under carefully controlled conditions. Examples of such processes include chemical vapor deposition and etching processes. Of particular concern is the uniformity of temperature and gas flow to ensure uniform results, e.g., deposition thickness, across a wafer.

The process of depositing layers on a semiconductor wafer (or substrate) usually involves placing the substrate within a thermal reactor chamber and holding the wafer within a stream of a reactant gas flowing across the surface of a wafer. The thermal reactor is heated by external lamps which pass infra-red radiation into the reactor chamber through upper and lower heating ports. The heating ports are covered by infra-red transparent cover members. The upper cover member is generally characterized by a central window portion and a flange portion. The flange portion serves to support the central window portion in the thermal reactor. During wafer processing stresses are created in the cover member due to a pressure differential across the cover and/or the thermal expansion due to heating of the central window portion. These

stresses tend to localize in the flange portion of the cover member.

SUMMARY OF THE INVENTION

A cover member for a semiconductor processing thermal reactor is disclosed. The cover member has a central quartz window portion and an outer flange portion. The central window portion has either an inward bow defining a concave outside surface, or an outward bow defining a convex outside surface. The centerline of the central window portion has a radius of curvature which when extended through the flange portion divides the flange portion into an upper flange section and a lower flange section. The upper and lower flange portions having substantially equal masses.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and is not limited by the figures of the accompanying drawings, in which like references indicate similar elements, and in which:

Figure 1A is a cross-sectional view of a thermal reactor in one embodiment of the present invention.

Figure 1B is a cross-sectional view of the infra-red transparent cover member of Figure 1A.

Figure 1C is an enlarged view of the flange portion of the cover member shown in Figure 1B.

Figure 2A is a thermal reactor cover member in another embodiment of the present invention.

Figure 2B is an enlarged view of the flange portion of the cover member shown in Figure 2A.

DETAILED DESCRIPTION

A quartz window for a thermal reactor is disclosed. In the following description, numerous specific details are set forth, such as material types, dimensions, etc., in order to provide a thorough understanding of the present invention. However, it will be obvious to one of ordinary skill in the art that the invention may be practiced without these specific details. In other instances, well-known structures and processing steps have not been shown in particular detail in order to avoid unnecessarily obscuring the present invention.

With reference to Figures 1A through 1C, a thermal reactor in one embodiment of the present invention is illustrated. Thermal reactor 100 is formed by a reactor vessel 102 defining a wafer reactor chamber 104. Chamber 102 is defined, in part, by a cover member 106 mounted below an upper heating source 108, and a lower member 110 mounted above a lower heating source 112. Cover member 106 and lower member 110 are generally made of quartz. Heating sources 108 and 112 provide infra-red radiant heat into the chamber through members 106 and 110 which are transparent to infra-red radiation. Cover member 106 includes a central window portion 114 and a peripheral flange portion 116 for supporting the central window portion. The window portion 106 generally has a spherical shape. As viewed from above, flange portion 116 generally has a circular shape. Central window portion 114 is typically made of a clear fused silica quartz whereas the flange portion is made of an opaque quartz. The flange is captured between a baseplate 118 and an upper clamp ring 120. Clamp ring 120 is secured to baseplate 118 by a suitable clamping means such as locking bolts 122. It is appreciated that cover member 116 may be made entirely of a single material, such as fused silica

quartz. Moreover, it is to be understood that the present invention is not limited to the manner in which the cover member is attached to the reactor housing.

In the embodiment illustrated in Figures 1A through 1C, central window portion 114 has an outward bow that forms a convex outside surface. The central window portion 114 has a centerline 160 having a curvature of radius. When extended through the flange portion 116 of cover member 106, the centerline 160 divides the flange portion into an upper flange section 170 and a lower flange section 172. The geometry's of central window portion 114 and flange portion 116 are configured such that the upper flange section 170 and the lower flange section 172 of flange portion 116 have substantially the same mass and/or cross-sectional area.

Cover member 106 is resiliently supported by a cushioning material such as base sealing rings 124 that are positioned between baseplate 118 and flange 116. Cover member 106 is further supported by clamp sealing o-rings 126 that are located between clamp ring 120 and flange 116. The o-rings are preloaded by the locking bolts 122 to provide a double seal for preventing the processing gas within chamber 104 from escaping into the ambient atmosphere. Lower member 110 also has a window portion 128 and a flange portion 130 that is similarly mounted between baseplate 118 and a lower clamp ring 132 with locking bolts 134 and o-rings 136 and 138.

Process gas enters chamber 104 through a gas inlet port 140 and exits the chamber through an exit port 142. The pressure of the gas within the chamber is maintained by metering the gas flow out of exit port 142.

A susceptor 144 is provided within chamber 104 for supporting a wafer 146. Susceptor 144 includes a mounting shaft 148 that is coupled to a motor (not shown). In this manner, wafer 148 may be rotated during processing to permit a more uniform heating and deposition.

As previously discussed, stresses in the cover member 106 are

generally localized in the outer flange portion of the cover member. A salient feature of the present invention lies in the construction of the cover member 106. The domed or bowed configuration of central window portion 114 causes the stress within central window portion 114 to be transmitted into the flange portion 116. The flange portion thus acts to resist the outward expansion of the domed cover member 106 due to a pressure differential across the cover and/or the thermal expansion due to heating of central window portion 114. Since the upper flange section 170 and lower flange section 172 have substantially the same mass and/or cross-sectional area, the resisting force within flange portion 116 is equally distributed between the upper and lower flange sections. By equally distributing the mass of the flange portion on opposing sides of the centerline 160, the structural strength of the flange portion is effectively increased since the resisting forces are essentially equally divided between the upper and lower sections of the flange.

The diameter of window portion 114 may vary significantly from one thermal reactor to another. In one exemplary embodiment window portion 114 has a diameter of 17.5 inches and a radius of curvature of 35 inches. Depending upon the specific application, the radius of curvature typically is in the range of 15 to 100 inches. The thickness of central window portion 114 is generally between of 0.1 to 0.2 inches. The thickness of flange portion 116 is in the range of 0.5 to 1.5 inches. Flange dimensions "A" and "B" are approximately 3.0 and 1.6 inches, respectively. Flange dimension "A" may vary between 2.0 and 3.5 inches. Flange dimension "B" may vary between 0.75 to 2.0 inches.

Turning now to Figures 2A and 2B, a thermal reactor cover member 206 in accordance with another embodiment of the present invention is shown. Cover member 206 includes a central window portion 214 and a flange portion 216. The central window portion 214 has an inward bow that forms a concave outside surface. Cover member 206 is typically used in ambient pressure or above-ambient

pressure thermal reactors. The central window portion 214 has a centerline 260 having a curvature of radius. When extended through the flange portion 216 of cover member 206, the centerline 260 divides the flange portion 216 into an upper flange section 270 and a lower flange section 272. The geometry's of central window portion 214 and flange portion 216 are configured such that the upper flange section 270 and the lower flange section 272 of flange portion 216 have substantially the same mass and/or cross-sectional area. As previously discussed, since the upper and lower flange sections have substantially the same mass and/or cross-sectional area, the resisting force within flange portion 216 is equally distributed between the upper and lower flange sections.

In one embodiment window portion 214 has a diameter of 17.5 inches. The radius of curvature of central window portion 114 is relatively large. In one embodiment, window portion 114 has a radius of curvature of 100 inches. Depending upon the specific application, the radius of curvature typically is in the range of 50 to 300 inches. The thickness of central window portion 114 is generally between of 0.1 to 0.2 inches. The thickness of flange portion 116 is in the range of 0.5 to 1.5 inches.

It is appreciated that the methods and apparatus of the present invention may be used for multiple wafer processing and single wafer processing. It is further understood that the relative dimensions, geometric shapes, materials and process techniques set forth within the specification are exemplary of the disclosed embodiments only. Whereas many alterations and modifications to the present invention will no doubt become apparent to a person ordinarily skilled in the art having read the foregoing description, it is to be understood that the particular embodiments shown and described by way of illustration are in no way intended to be limiting. Therefore, reference to the details of the illustrated diagrams is not intended to limit the scope of the claims which themselves recite only those features regarded as essential to the invention.

CLAIMS

What is claimed is:

1. An infra-red transparent cover member for a thermal reactor comprising:
 - a central window portion having a centerline, the centerline having a radius of curvature; and
 - a flange portion, the centerline of the central window portion when extended through the flange portion dividing the flange portion into an upper flange section and a lower flange section, the upper and lower flange sections having substantially the same cross-sectional area.
2. The cover member of claim 1 wherein the central window portion has an outward bow defining a convex outside surface.
3. The cover member of claim 1 wherein the central window portion has an inward bow defining a concave outside surface.
4. The cover member of claim 1 wherein the central window portion is made of clear fused silica quartz.
5. The cover member of claim 1 wherein the flange portion is made of opaque silica quartz.
6. The cover member of claim 2 wherein the radius of curvature of the central window portion is in the range of 15 to 100 inches.
7. The cover member of claim 3 wherein the radius of curvature of the central window portion is in the range of 50 to 300 inches.
8. A thermal reactor for processing a semiconductor wafer comprising:

a wafer chamber for containing at least one semiconductor wafer during processing;

a window member at least partially defining the wafer chamber, the window member comprising a flange portion and a central window portion having a center line with a radius of curvature, the center line of the central window portion when extended through the flange portion dividing the flange portion into an upper flange section and a lower flange section, the upper and lower flange sections having substantially the same cross-section area.

9. The cover member of claim 8 wherein the central window portion has an outward bow defining a convex outside surface.

10. The cover member of claim 8 wherein the central window portion has an inward bow defining a concave outside surface.

11. The cover member of claim 8 wherein the central window portion is made of clear fused silica quartz.

12. The cover member of claim 8 wherein the flange portion is made of opaque silica quartz.

13. The cover member of claim 9 wherein the radius of curvature of the central window portion is in the range of 15 to 100 inches.

14. The cover member of claim 10 wherein the radius of curvature of the central window portion is in the range of 50 to 300 inches.




FIG. 1 A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/16583

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H01L21/00 C23C16/48

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01L C23C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 474 251 A (APPLIED MATERIALS INC) 11 March 1992 (1992-03-11) abstract; claims; figures column 1, line 10 -column 2, line 48 column 3, line 28 - line 57 column 4, line 20 -column 7, line 55 column 8, line 15 - line 51	1,2,4,6, 8,9,11
X	EP 0 675 524 A (APPLIED MATERIALS INC) 4 October 1995 (1995-10-04) abstract; figure 1 column 4, line 11 - line 55	1,2,4,8, 9,11
P,X, L	WO 99 07925 A (APPLIED MATERIALS INC) 18 February 1999 (1999-02-18) the whole document (L: Priority)	1-14

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

3 December 1999

Date of mailing of the international search report

10/12/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hamdani, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/16583

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	FR 2 763 964 A (SGS THOMSON MICROELECTRONICS) 4 December 1998 (1998-12-04) page 2, line 12 - line 30; figure 1 ---	1,2,4,6, 8,9,11, 13
P, X, L	US 5 916 370 A (CHANG CHOW LING) 29 June 1999 (1999-06-29) column 1, line 13 - line 33; figures 1,4 column 2, line 29 - line 45 (L: Priority) -----	1,2,4,8, 9,11

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/US 99/16583

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0474251 A	11-03-1992	US 5085887 A DE 69106285 D DE 69106285 T JP 4245420 A JP 7089542 B	04-02-1992 09-02-1995 24-08-1995 02-09-1992 27-09-1995
EP 0675524 A	04-10-1995	US 5551982 A JP 8055842 A US 5834059 A US 5599397 A US 5725673 A	03-09-1996 27-02-1996 10-11-1998 04-02-1997 10-03-1998
WO 9907925 A	18-02-1999	NONE	
FR 2763964 A	04-12-1998	NONE	
US 5916370 A	29-06-1999	NONE	